

**List of products available to be delivered from suppliers stock**

<b>Crt No.</b>	<b>Items denomination</b>	<b>U/M</b>	<b>Quantity</b>	<b>Manuf. Year</b>	<b>Remarks</b>																
<b>0</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>																
1	RACOV Linking Device for 7.62 x 54 mm. cartridges	pcs	77	2008																	
2	14.5x114 mm APIT (BZT) cartridges	pcs	62.000	1998	<table border="1"> <thead> <tr> <th colspan="2">SPECIFICATIONS</th> </tr> </thead> <tbody> <tr> <td>Muzzle velocity</td> <td>995 – 1015 m/s</td> </tr> <tr> <td>Weight of bullet</td> <td>59 g</td> </tr> <tr> <td>Average max. pressure</td> <td>3300 daN/cm<sup>2</sup></td> </tr> <tr> <td>Cartridge case</td> <td>steel</td> </tr> <tr> <td>Bullet</td> <td>steel core</td> </tr> <tr> <td>Primer</td> <td>Berdan</td> </tr> <tr> <td>Armour penetration</td> <td>20 mm at 100 m</td> </tr> </tbody> </table>	SPECIFICATIONS		Muzzle velocity	995 – 1015 m/s	Weight of bullet	59 g	Average max. pressure	3300 daN/cm <sup>2</sup>	Cartridge case	steel	Bullet	steel core	Primer	Berdan	Armour penetration	20 mm at 100 m
SPECIFICATIONS																					
Muzzle velocity	995 – 1015 m/s																				
Weight of bullet	59 g																				
Average max. pressure	3300 daN/cm <sup>2</sup>																				
Cartridge case	steel																				
Bullet	steel core																				
Primer	Berdan																				
Armour penetration	20 mm at 100 m																				
3	7.62 x 39 mm blank cartridges	pcs	8.503.400	2005-2006																	
4	7.62 x 54 mm blank cartridges	pcs	350.000	2005-2006																	
5	Composition B (Explosives Category)	kg	20.000	2008	<table border="1"> <thead> <tr> <th colspan="2">SPECIFICATIONS</th> </tr> </thead> <tbody> <tr> <td>RDX content</td> <td>59.5 ± 2.0 %</td> </tr> <tr> <td>TNT content</td> <td>39.5 ± 2.3 %</td> </tr> <tr> <td>Desensitizing agent</td> <td>1.0 ± 0.3 %</td> </tr> <tr> <td>Humidity</td> <td>max 0.2 %</td> </tr> <tr> <td>Insoluble particles retained by USS no 60 sieve (according to MIL-C-401E)</td> <td>max 5</td> </tr> </tbody> </table>	SPECIFICATIONS		RDX content	59.5 ± 2.0 %	TNT content	39.5 ± 2.3 %	Desensitizing agent	1.0 ± 0.3 %	Humidity	max 0.2 %	Insoluble particles retained by USS no 60 sieve (according to MIL-C-401E)	max 5				
SPECIFICATIONS																					
RDX content	59.5 ± 2.0 %																				
TNT content	39.5 ± 2.3 %																				
Desensitizing agent	1.0 ± 0.3 %																				
Humidity	max 0.2 %																				
Insoluble particles retained by USS no 60 sieve (according to MIL-C-401E)	max 5																				
6	PKT 7.62x54mm machine gun, tank version, with accessories, ctg. I	pcs	13																		
7	DShKM 12.7x108 mm heavy machine gun, tank version, with accessories, ctg. I	pcs	78																		
8	DShKM 12.7x108 mm heavy machine gun, tank version, with accessories, ctg. I	pcs	3		tropicalized version																

Note:

Ctg. I - Unused